

TEMPOMATIC PRO electronic tap

Ref. 44525715

Battery-operated, Ø 15mm conical inlet

DESCRIPTION

TEMPOMATIC PRO electronic tap - Ref.44525715

Deck-mounted electronic basin tap:
Independent IP65 electronic control unit.
Battery-operated with 123 6V Lithium batteries.
Flow rate pre-set at 4 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
Shock-resistant infrared presence detection sensor.
Chrome-plated solid brass body with fixing reinforced by 2 stainless steel rods.
PEX flexible with filter and solenoid valve Ø 15mm for compression fittings.
360° swivelling spout with smooth interior (reduces bacterial development).
Removable spout for cleaning.
Anti-blocking security.
Suitable for people with reduced mobility.
10-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC PRO electronic tap - Ref.44525715

Technology	Electronic
Debit	3 lpm
Conector	M1/2" Ø 15mm
Supply	6V battery
Supply	6V batteries
Drop Height	310 mm
Spout Length	200 mm
Installation:	Deck-mounted



ADVANTAGES



Total hygiene: no manual contact



85% water savings



Independent IP65 electronic control unit



Duty flush limits bacterial proliferation

