DELABIE

BINOPTIC MIX electronic mixer



Ref. 388MCHLH

Mains supply

DESCRIPTION

BINOPTIC MIX electronic mixer - Ref.388MCHLH

Deck-mounted electronic basin mixer:
Independant IP65 electronic unit.
230/12V mains supply with transformer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set at 60 seconds every 24 hours after the last use).
Optimised active infrared presence detection at the end of the spout.
Body in chrome-plated brass.
PEX flexibles with filters and M3/8" solenoid valves.
Fixings reinforced by 2 stainless steel rods.
Anti-blocking security.
Spout with smooth interior and low water volume (reduces niches where bacteria can develop).
Side temperature control lever with long lever and adjustable maximum temperature limiter.
Drop height: 170mm, for semi-recessed basins.
Suitable for people with reduced mobility.
10-year warranty.


ADVANTAGES

- Total hygiene: no manual contact
- 90% water savings
- Sleek design
- Anti-bacterial proliferation duty flush

TECHNICAL CHARACTERISTICS

BINOPTIC MIX electronic mixer - Ref.388MCHLH

Technology	Electronic
Debit	3 lpm
Conector	M3/8"
Supply	230/12V mains supply
Drop Height	170 mm
Spout Length	175 mm
Installation:	Deck-mounted



© Delabie