DELABIE

BINOPTIC MIX electronic mixer



Ref. 498MCHLH15

Battery-operated, Ø 15mm conical inlets

DESCRIPTION

BINOPTIC MIX electronic mixer - Ref.498MCHLH15

Deck-mounted electronic basin mixer:
Independent IP65 electronic control unit.
123 6V Lithium batteries.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush 60 seconds every 24 hours after last use).
Active, infrared presence detection, sensor at the end of the spout optimises detection.
Chrome-plated brass body.
PEX flexibles with filters and solenoid valves Ø 15mm for compression fittings.
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Spout with smooth interior and low water volume (reduces bacterial development).
Side temperature control with long lever and adjustable maximum temperature limiter.
Drop height: 250mm for counter-top washbasins.
Suitable for people with reduced mobility.
10-year warranty.


ADVANTAGES

- 90% water savings
- Total hygiene: no manual contact
- Sleek design
- Anti-bacterial proliferation duty flush

TECHNICAL CHARACTERISTICS

BINOPTIC MIX electronic mixer - Ref.498MCHLH15

Technology	Electronic
Debit	3 lpm
Conector	M1/2" Ø 15mm
Supply	6V batteries
Drop Height	250 mm
Spout Length	185 mm
Installation:	Deck-mounted



© Delabie