DELABIE

BINOPTIC electronic tap



Ref. 398015

Mains

DESCRIPTION

BINOPTIC electronic tap - Ref.398015

Deck-mounted electronic basin tap:
Independent IP65 electronic control unit.
230/12V mains supply with transformer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
Active, infrared presence detection, sensor at the end of the spout optimises detection.
Chrome-plated brass body.
PEX flexible with filter and solenoid valve M?".
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Spout with smooth interior and low water volume (reduces bacterial development).
Drop height: 250mm for countertop washbasins.
Suitable for people with reduced mobility.
10-year warranty.


ADVANTAGES

- 90% water savings
- Total hygiene: no manual contact
- Sleek design
- Anti-bacterial proliferation duty flush

TECHNICAL CHARACTERISTICS

BINOPTIC electronic tap - Ref.398015

Technology	Electronic
Debit	3 lpm
Conector	M3/8"
Supply	230/12V mains supply
Drop Height	250 mm
Spout Length	185 mm
Installation:	Deck-mounted



© Delabie