

SECURITHERM

Securitouch thermostatic shower mixer

Ref. H9769

Thermostatic shower mixer with no non-return valves



DESCRIPTION

SECURITHERM Securitouch thermostatic shower mixer - Ref.H9769

SECURITHERM dual control thermostatic shower mixer.
 Thermostatic mixer with no non-return valves on the inlets (reduced bacterial proliferation).
 No risk of cross flow between hot and cold water.
 Anti-scalding failsafe: shuts off automatically if cold supply fails.
 Prevents cold showers: shuts off automatically if hot water supply fails.
 Securitouch thermal insulation prevents burns.
 Scale-resistant thermostatic cartridge for temperature adjustment.
 ¼-turn ceramic head for flow rate adjustment.
 Temperature control up to 41°C.
 Double temperature limiter: 1st limiter set at 38°C, 2nd limiter set at 41°C.
 Thermal shocks are possible without removing the control knob or shutting off the cold water supply.
 Flow rate limited to 9 lpm at 3 bar.
 Ergonomic controls.
 M½" shower outlet.
 F¾" inlets with integrated filters.
 Mixer supplied with offset STOP/CHECK wall connectors M½" M¾".
 Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics
 10-year warranty.

ADVANTAGES

TECHNICAL CHARACTERISTICS

SECURITHERM Securitouch thermostatic shower mixer - Ref.H9769

Technology	SECURITHERM dual control thermostatic mixer, Securitouch, no non-return valves
Lungime	260 mm
Debit	8 lpm
Conector	M1½"
Finisaj	Chrome-plated brass
Temperature limiter	41 °C
Depth	95 mm

