

## SECURITHERM shower panel

Ref. H963615

Thermostatic shower panel with mixer and no non-return valves



### DESCRIPTION

#### SECURITHERM shower panel - Ref.H963615

SECURITHERM anodised aluminium shower panel for wall-mounted exposed installation.

SECURITHERM thermostatic sequential shower mixer (non-time flow).

Thermostatic sequential shower mixer: opens and closes with cold water.

Mixer with no non-return valves on the inlets (reduces bacterial proliferation).

No risk of cross flow between the hot and cold water.

Sequential mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails.

Cold water failsafe prevents cold showers: shuts off automatically if hot water supply fails.

Temperature control from cold water up to 39°C.

Temperature limiter set at 39°C, can be adjusted.

Thermal shocks are possible.

Flow rate 9 lpm at 3 bar.

Sliding handset on chrome-plated rail with flexible shower hose removable with push fit rapid STOP connector.

Hygiene control lever L. 100mm.

Top inlets with M1/2" inline stopcocks.

Copper tubes.

Concealed fixings. Filters.

Shower panel suitable for healthcare facilities, retirement and care homes, hospitals and clinics.

Suitable for people with reduced mobility.

10-year warranty.

### ADVANTAGES



SECURITHERM: Optimum anti-scalding safety



Maximum hygiene: no non-return valves



Thermostatic: total temperature stability



Sequential: open and closing on cold water

## TECHNICAL CHARACTERISTICS

### SECURITHERM shower panel - Ref.H963615

Technology	SECURITHERM single control thermostatic mixer
Inaltime	1045 mm
Debit	9 lpm
Conector	M1/2" Ø 15mm
Finisaj	Aluminium
Supply	Top inlets via inline stopcocks M1/2"
Temperature limiter	39 °C
Width	210 mm
Water supply	Concealed

