

SECURITHERM

Securitouch thermostatic shower mixer

Ref. 9769

Thermostatic mixer with no non-return valves



DESCRIPTION

SECURITHERM Securitouch thermostatic shower mixer - Ref.9769

SECURITHERM dual control thermostatic shower mixer.
Thermostatic mixer with no non-return valves on the inlets (reduces bacterial proliferation).
No risk of cross flow between the hot and cold water.
Anti-scalding failsafe: shuts off automatically if cold water supply fails.
Prevents cold showers: shuts off automatically if hot water supply fails.
Securitouch thermal insulation prevents burns.
Scale-resistant thermostatic cartridge to adjust the temperature.
1/4-turn ceramic head for flow rate adjustment.
Temperature control up to 41°C.
Double temperature limiter: first limiter set at 38°C can be overridden, second limiter set at 41°C.
Thermal shocks are possible without removing the control knob or shutting off the cold water supply.
Flow rate limited to 9 lpm at 3 bar.
ERGO control knobs.
M1/2" shower outlet.
F3/4" inlets with integrated filters.
Mixer with no wall connectors.
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics
10-year warranty.

ADVANTAGES

TECHNICAL CHARACTERISTICS

SECURITHERM Securitouch thermostatic shower mixer - Ref.9769

Technology	SECURITHERM dual control thermostatic mixer, Securitouch, with no non-return valves
Lungime	260 mm
Debit	9 lpm
Conector	M1/2"
Finisaj	Chrome-plated brass
Temperature limiter	41 °C

