

SECURITHERM securitouch thermostatic auto-drain shower kit

Ref. H9739HYG

Dual control thermostatic mixer



DESCRIPTION

SECURITHERM securitouch thermostatic auto-drain shower kit -

Ref.H9739HYG

SECURITHERM dual control thermostatic shower kit with auto-draining device includes:

- Mixer with scale-resistant, thermostatic cartridge:
 - Anti-scalding failsafe: shuts off automatically if cold or hot water supply fails.
 - Temperature control from 25 - 40°C with maximum temperature limiter set at 38°C.
 - 1/4-turn ceramic head for flow rate adjustment.
 - Thermal shocks are possible without removing the control knob or shutting off the cold water supply.
 - Flow rate regulated at 9 lpm.

CLASSIC control knobs.

M1/2" shower outlet.

- F3/4" inlets with integrated filters and non-return valves.
- Supplied with 2 STOP/CHECK wall connectors, M1/2" M3/4", ideal for hospitals.

- Shower head (ref. 813) with flexible shower hose (ref. 836T3) and chrome-plated wall-mounted adjustable support (ref. 845) and tilting shower head holder (ref. 845).

- Auto-draining device FM1/2" for installation between the flexible hose and the shower head, automatically drains the shower head and flexible hose (reduces bacterial development) (ref. 880).

10-year warranty.

ADVANTAGES

TECHNICAL CHARACTERISTICS

SECURITHERM securitouch thermostatic auto-drain shower kit -

Ref.H9739HYG

Technology	SECURITHERM dual control thermostatic mixer
Inaltime	86 mm
Debit	9 lpm
Conector	M1/2"
Finisaj	Chrome-plated brass
Temperature limiter	38 °C
Depth	281 mm

