

TEMPOMATIC 2 electronic tap

Ref. 444006

Battery-operated



DESCRIPTION

TEMPOMATIC 2 electronic tap - Ref.444006

Deck-mounted electronic basin tap:
 Independent IP65 electronic control unit.
 Battery-operated with 123 6V Lithium batteries.
 Flow rate pre-set at 4 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
 Scale-resistant flow straightener.
 Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
 Shock-resistant infrared presence detection sensor.
 Chrome-plated solid brass body.
 PEX flexible with filter and reduced-stagnation solenoid valve M3/8".
 Fixing reinforced by 2 stainless steel rods.
 Anti-blocking security.
 Suitable for people with reduced mobility.
 10-year warranty.

ADVANTAGES



Total hygiene: no manual contact



85% water savings



Independent IP65 electronic control unit



Anti-bacterial proliferation duty flush

TECHNICAL CHARACTERISTICS

TEMPOMATIC 2 electronic tap - Ref.444006

Technology	Electronic
Debit	4 lpm
Conector	M3/8"
Supply	6V battery
Supply	6V batteries
Drop Height	125 mm
Spout Length	145 mm
Installation:	Deck-mounted

