

## SECURITHERM shower panel

Ref. 792410

Electronic battery-operated thermostatic







### DESCRIPTION

#### SECURITHERM shower panel - Ref.792410

Electronic thermostatic shower panel:  
 Anodised aluminium shower panel for wall-mounted, exposed installation.  
 With concealed inlet via flexibles, M1/2".  
 SECURITHERM thermostatic mixer.  
 Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.  
 Anti-scalding failsafe: automatic shut-off if cold water fails.  
 Anti-cold showers function: automatic shut-off if hot water fails.  
 Thermal shocks are possible.  
 Battery-operated with 223 6V Lithium battery.  
 Infrared presence detection. Shower starts when hand is 4cm from the sensor.  
 Shuts off on demand or automatically after ~60 seconds.  
 Duty flush (~60 seconds every 24 hours after the last use).  
 Flow rate set at 6 lpm at 3 bar.  
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.  
 Concealed fixings.  
 Filters and non-return valves.  
 Suitable for people with reduced mobility.  
 10-year warranty.

### ADVANTAGES

-  80% water savings
-  Anti-bacterial proliferation duty flush
-  Immediate shut-off if cold water fails
-  Sleek shapes, concealed fixings

### TECHNICAL CHARACTERISTICS

#### SECURITHERM shower panel - Ref.792410

Technology	Electronic
Inaltime	1050 mm
Debit	6 lpm
Conector	M1/2"
Finisaj	Aluminium
Supply	6V battery
Temperature limiter	Thermostatic
Width	210 mm
Depth	65 mm
Water supply	Concealed

