DELABIE

SECURITHERM shower panel

Ref. 792413

Electronic battery-operated thermostatic



DESCRIPTION

SECURITHERM shower panel - Ref.792413

SECURITHERM electronic thermostatic shower panel:
Large stainless steel panel for wall-mounted, exposed installation.
Concealed inlet via flexibles M½".
SECURITHERM thermostatic mixer.
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
Anti-scalding failsafe: automatic shut-off if cold water fails.
Anti-cold showers function: automatic shut-off if hot water fails.
Thermal shocks are possible.
Battery-operated with 223 6V Lithium battery.
Shower starts when hand is 4cm from the infrared sensor.
Shuts off on demand or automatically after ~60 seconds.
Duty flush (~60 seconds every 24 hours after the last use).
Flow rate 6 lpm at 3 bar.
Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
Concealed fixings.
Filters and non-return valves.
M½" stopcocks.
Suitable for people with reduced mobility.
10-year warranty.


ADVANTAGES

- Total hygiene: operate without manual contact
- Automatic anti-bacterial duty flush
- Thermostatic temperature regulation
- Instant shut-off if cold water fails

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref.792413

Technology	Electronic
Inaltime	1220 mm
Debit	6 lpm
Conector	M1/2"
Finisaj	Stainless steel
Supply	6V battery
Temperature limiter	Thermostatic
Width	250 mm
Depth	100 mm
Water supply	Concealed



© Delabie