

## SECURITHERM shower panel

Ref. 792413CF

Electronic thermostatic battery-operated







### DESCRIPTION

#### SECURITHERM shower panel - Ref.792413CF

SECURITHERM electronic thermostatic shower panel:  
 Large model stainless steel panel for wall-mounted, exposed installation.  
 Concealed inlet via flexibles M $\frac{1}{2}$ ".  
 SECURITHERM thermostatic mixer.  
 Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.  
 Anti-scalding failsafe: automatic shut-off if cold water fails.  
 Anti-cold showers function: automatic shut-off if hot water fails.  
 Thermal shocks are possible.  
 Battery-operated with 223 6V Lithium battery.  
 Shower starts when hand is 4cm from the infrared sensor.  
 Shuts off voluntarily or automatically after ~60 seconds.  
 Duty flush (~60 seconds every 24 hours after last use).  
 Flow rate 6 lpm at 3 bar.  
 Chrome-plated, tamperproof ROUND shower head with scale-resistant nozzle and automatic flow rate regulation.  
 Concealed fixings.  
 Filters and non-return valves.  
 M $\frac{1}{2}$ " stopcocks.  
 Suitable for people with reduced mobility.  
 10-year warranty.

### ADVANTAGES

-  Total hygiene: operate without manual contact
-  Duty flush prevents bacterial proliferation
-  Thermostatic temperature regulation
-  Immediate shut-off if cold water fails

### TECHNICAL CHARACTERISTICS

#### SECURITHERM shower panel - Ref.792413CF

Technology	Electronic
Inaltime	1220 mm
Debit	6 lpm
Conector	M1/2"
Finisaj	Stainless steel
Supply	6V battery
Temperature limiter	Thermostatic
Width	250 mm
Depth	100 mm
Water supply	Concealed

