

SECURITHERM shower panel

Ref. 792330

Thermostatic time flow dual control

DESCRIPTION

SECURITHERM shower panel - Ref.792330

SECURITHERM dual control thermostatic time flow shower panel:
 Anodised aluminium shower panel for wall-mounted, exposed installation.
 With concealed inlet via flexibles, M $\frac{1}{2}$ ".
 SECURITHERM thermostatic mixer.
 Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
 Anti-scalding failsafe: automatic shut-off if cold water fails.
 Anti-cold showers function: automatic shut-off if hot water fails.
 Thermal shocks are possible.
 Time flow valve ~30 seconds with soft-touch operation.
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.
 Handset with removable flexible via push-fit rapid STOP connector and wall support supplied.
 Concealed fixings.
 Filters and non-return valves.
 Suitable for people with reduced mobility.
 10-year warranty.





TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref.792330

Technology	Time flow
Inaltime	1050 mm
Debit	6 lpm
Conector	M1/2"
Finisaj	Aluminium
Temperature limiter	Thermostatic
Width	210 mm
Depth	67 mm
Water supply	Concealed



ADVANTAGES

-  Thermostatic temperature regulation
-  Instant shut-off if cold water fails
-  80% water savings
-  Aluminium panel, brass controls

