

SECURITHERM shower panel

Ref. 79239015

Thermostatic mechanical dual control

DESCRIPTION

SECURITHERM shower panel - Ref.79239015

Dual control thermostatic shower panel:
Anodised aluminium shower panel for wall-mounted, exposed installation.
Top inlet via in-line stopcocks and conical Ø 15mm inlets.
SECURITHERM thermostatic mixer.
Adjustable temperature control from cold water to 41°C.
Anti-scalding safety: automatic shut-off if cold or hot water supply fails.
Anti-cold showers function: automatic shut-off if hot water fails.
Thermal shocks are possible.
1/4 turn non-time flow valves.
Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation set at 6 lpm at 3 bar.
Handset with removable flexible via rapid push-fit connector and wall-support supplied.
Concealed fixings.
Filters and non-return valves.
Suitable for people with reduced mobility.
10-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref.79239015

Technology	Non-time flow
Inaltime	1050 mm
Debit	6 lpm
Conector	M1/2" Ø 15mm
Finisaj	Aluminium
Temperature limiter	Thermostatic
Width	210 mm
Depth	65 mm
Water supply	In-line



ADVANTAGES



Thermostatic control



Instant shut-off if cold water fails



Fixed shower head or handset



Aluminium panel, brass controls

