

TEMPOFIX 3 self-supporting frame system with time flow WC valve

Ref. 564065-763040

TEMPOFLUX 3 AB dual flush 3L/6L time flow valve

DESCRIPTION

TEMPOFIX 3 self-supporting frame system with time flow WC valve -

Ref.564065-763040

Self-supporting frame system for wall-hung WC pans:

- Black powder-coated steel frame.
- Fixes to load-bearing floors.
- Frame height can be adjusted from 0 - 200mm (with 1m mark).
- Ø 32mm flush tube with Ø 55mm connection washer.
- Ø 100mm PVC soil pipe to glue on to waterproof seal, with 2 setting positions.
- Delivered pre-mounted.
- Compatible with solid walls from 10 - 120 mm.
- 10-year warranty.

Fitted with a TEMPOFLUX 3 F $\frac{3}{4}$ " time flow direct flush valve:

- Chrome-plated metal wall plate 170 x 170mm.
- Waterproof recessing housing.
- Soft-touch operation.
- Dual flush 3L/6L, can be adjusted to 2L/4L.
- AB anti-blocking system.
- Backflow prevention device inside the housing.
- Integrated stopcock and flow rate adjuster.
- Acoustic level complies with NF EN 12541 class II.
- Compatible with sea water and grey water.

For technical features see TEMPOFLUX 3 ref. 763BOX-763000.

Kit contents:

(564065): frame system, soil pipe Ø 100mm, flush tube, recessed housing with cover, valve for system flush, vacuum breaker, stopcock, connection accessories.

(763040): control plate, collar for waterproofing, time flow cartridge.



ADVANTAGES



Quick and easy to install:
delivered pre-mounted



Self-supporting frame system



Dual flush 3L/6L, anti-
blocking system



Direct flush: no stagnant
water

TECHNICAL CHARACTERISTICS

TEMPOFIX 3 self-supporting frame system with time flow WC valve -

Ref.564065-763040

Technology	Time flow
Inaltime	1000 - 1320 mm
Conector	3/4"
Finisaj	Chrome-plated metal
Width	350 mm
Depth	157 - 177 mm

