

TEMPOFIX 3 self-supporting frame system with time flow WC valve

Ref. 578405-578222

3L/6L dual flush time flow valve



DESCRIPTION

TEMPOFIX 3 self-supporting frame system with time flow WC valve -

[Ref.578405-578222](#)

Self-supporting frame system for wall-hung WCs:

- Black powder-coated steel frame.
- Fixes to load-bearing floors.
- Frame height can be adjusted from 0 - 200mm (with 1m mark).
- Ø 32mm flush tube with Ø 55mm connection washer.
- Ø 100mm soil pipe and PVC collar with waterproof seal, with 2 settings positions.
- Delivered pre-mounted.
- For semi-thick walls 30 - 60mm.
- 10-year warranty.

Fitted with TEMPOFLUX 2 direct flush time flow valve:

- Ø 195mm chrome-plated wall plate with concealed fixings.
- 3L/6L dual flush (can be adjusted to 2L/4L).
- Soft-touch operation.
- Vacuum breaker.
- Stopcock and flow rate/volume adjuster.
- Solid brass body and shock-resistant, scale-resistant mechanism.
- In-line inlet M3/4".
- Acoustic level complies with European standard EN 12541 class II.

TECHNICAL CHARACTERISTICS

TEMPOFIX 3 self-supporting frame system with time flow WC valve -

[Ref.578405-578222](#)

| Technology | Time flow |
|------------|---------------------|
| Inaltime | 1000 - 1320 mm |
| Conector | 3/4" |
| Finisaj | Chrome-plated metal |
| Width | 350 mm |
| Depth | 157 - 177 mm |

ADVANTAGES



Easy and quick to install: supplied pre-mounted



Self-supporting frame system



3L/6L dual flush, can be adjusted to 2L/4L



Direct flush: no water stagnation