

TEMPOFIX 3 wall-mounted frame system for WCs

Ref. 578300DE-578212

6L single flush time flow valve - Ø 110mm soil pipe



DESCRIPTION

TEMPOFIX 3 wall-mounted frame system for WCs -

Ref.578300DE-578212

Wall-mounted frame system W. 350mm for wall-hung WCs:

- Black powder-coated steel frame.
- Fixes to load-bearing walls.
- Frame height can be adjusted from 0 - 200mm (with 1m mark).
- Ø 32mm flush tube with Ø 55mm connection washer.
- Ø 110mm HDPE soil pipe with waterproof seal, with 2 settings positions.
- Delivered pre-mounted.
- For walls 10 - 35mm.
- 10-year warranty.

Fitted with TEMPOFLUX 2 time flow direct flush valve:

- Ø 195mm chrome-plated metal wall plate with concealed fixings.
- 6L single flush.
- Soft-touch operation.
- Vacuum breaker.
- Stopcock and flow rate/volume adjuster.
- Solid brass body and shock-resistant, scale-resistant mechanism.
- In-line inlet M $\frac{3}{4}$ ".
- Complies with European standard EN class II.

Technical features: see TEMPOFLUX 2 ref. 762901.

Kit contents:

(578300DE): frame system, soil pipe Ø 110mm, flush tube, valve with cover, vacuum breaker, connection accessories.

(578212): control plate, fixings.

TECHNICAL CHARACTERISTICS

TEMPOFIX 3 wall-mounted frame system for WCs -

Ref.578300DE-578212

Technology	Time flow
Inaltime	1000 - 1320 mm
Conector	3/4"
Finisaj	Chrome-plated metal
Width	350 mm
Depth	170 - 190 mm

ADVANTAGES



Easy and quick to install: supplied pre-mounted



Install behind wall



Soft-touch operation



Direct flush: no water stagnation

