

TEMPOFIX 3 self-supporting frame system with time flow WC valve

Ref. . 564065BE-763000

TEMPOFLUX 3 AB dual flush 3L/6L time flow valve - Ø 90mm soil pipe



DESCRIPTION

TEMPOFIX 3 self-supporting frame system with time flow WC valve -

Ref.. 564065BE-763000

Self-supporting frame system W. 350mm for wall-hung WCs:

- Black powder-coated steel frame.
- Fixes to load-bearing floors.
- Frame height can be adjusted from 0 - 200mm (with 1m mark).
- Ø 32mm flush tube with Ø 55mm connection washer.
- Ø 90mm ABS soil pipe with waterproof seal, with 2 setting positions.
- Delivered pre-mounted.
- Compatible with solid walls from 10 - 120 mm.
- 10-year warranty.

Fitted with a TEMPOFLUX 3 F3/4" time flow direct flush valve:

- Satin finish stainless steel wall plate 210 x 162mm.
- Waterproof recessing housing.
- Soft-touch operation.
- Dual flush 3L/6L, can be adjusted to 2L/4L.
- AB anti-blocking system.
- Backflow prevention device inside the housing.
- Integrated stopcock and flow rate adjuster.
- Acoustic level complies with NF EN 12541 class II.
- Compatible with sea water and grey water.

Technical characteristics: see TEMPOFLUX 3 ref. 763BOX-763000.

Kit contents:

(564065BE): frame system, soil pipe Ø 90mm, flush tube, recessed housing with cover, valve configured for system flush, vacuum breaker, stopcock, connection accessories.

(763000): control plate, collar for waterproofing, time flow cartridge.

ADVANTAGES

TECHNICAL CHARACTERISTICS

TEMPOFIX 3 self-supporting frame system with time flow WC valve -

Ref.. [564065BE-763000](#)

Technology	Time flow
Inaltime	1000 - 1320 mm
Conector	3/4"
Finisaj	Stainless steel satin finish
Width	350 mm
Depth	170 - 190 mm