

## TEMPOFIX 3 wall-mounted frame system with electronic WC valve

Ref. 564000DE-464000

TEMPOMATIC mains - dual control electronic valve - Ø 110mm soil pipe

### DESCRIPTION

**TEMPOFIX 3 wall-mounted frame system with electronic WC valve -**

**Ref.564000DE-464000**

Frame system W. 350mm for wall-hung WC pans:

- Black powder-coated steel frame.
- Fixes to load-bearing walls.
- Frame height can be adjusted from 0 - 200mm (with 1m mark).
- Ø 32mm flush tube with Ø 55mm connection washer.
- ABS soil pipe, Ø 110mm HDPE outlet with waterproof seal, with 2 setting positions.
- Delivered pre-mounted.
- Compatible with solid walls from 10 - 120 mm.
- 10-year warranty.

Fitted with a TEMPOMATIC dual control F3/4" electronic direct flush valve:

- Mains supply 230/6V cable and transformer supplied).
- Satin finish stainless steel wall plate 186 x 186mm and chrome-plated metal button.
- Shock-resistant infrared presence detection sensor.
- Waterproof recessing housing.
- Detection delay is 10 seconds.
- Voluntary activation (push-button with anti-blocking) or automatically when the user leaves.
- 3 programmes (rinsing volume can be set according to type of WC pan.
- Hygienic duty flush every 24 hours (can be adjusted to 12 hours or OFF) after the last use.

Technical characteristics: see TEMPOMATIC dual control ref. 464SBOX-464000.

Kit contents:

(564000DE): frame system, soil pipe Ø 110mm, flush tube, recessed housing with cover, valve configured for system flush, vacuum breaker, stopcock, connection accessories.

(464000): control plate, transformer, collar for waterproofing, solenoid valve, cartridge.



### ADVANTAGES



Total hygiene: no manual contact



Quick and easy to install: delivered pre-mounted



Direct flush: no stagnant water



Voluntary or automatic flush

## TECHNICAL CHARACTERISTICS

### TEMPOFIX 3 wall-mounted frame system with electronic WC valve -

Ref.564000DE-464000

Technology	Electronic and time flow
Inaltime	1000 - 1320 mm
Conector	3/4"
Finisaj	Stainless steel satin finish
Width	350 mm
Depth	170 - 190 mm

