

## TEMPOMATIC MIX 3 electronic mixer

Ref. 492006LH

Integrated battery, stopcocks

### DESCRIPTION

#### TEMPOMATIC MIX 3 electronic mixer - Ref.492006LH

Deck-mounted electronic basin mixer:  
Battery-operated with integrated 223 6V Lithium batteries.  
Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
Scale-resistant flow straightener.  
Duty flush (~60 seconds every 24 hours after last use).  
Active, infrared presence detection, sensor at the end of the spout optimises detection.  
Chrome-plated solid brass body.  
Cap fixed in place by 2 concealed screws, with pictogram to easily identify sensor.  
PEX flexibles with stopcocks, filters and non-return valves.  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Side temperature control with long lever and adjustable maximum temperature limiter.  
Suitable for people with reduced mobility.  
10-year warranty.

### TECHNICAL CHARACTERISTICS

#### TEMPOMATIC MIX 3 electronic mixer - Ref.492006LH

|               |              |
|---------------|--------------|
| Technology    | Electronic   |
| Debit         | 3 lpm        |
| Conector      | F3/8"        |
| Supply        | 6V battery   |
| Supply        | 6V batteries |
| Drop Height   | 100 mm       |
| Spout Length  | 120 mm       |
| Installation: | Deck-mounted |



### ADVANTAGES



Total hygiene: no manual contact



90% water savings



Battery integrated into the body of the tap



Anti-bacterial proliferation duty flush

