

TEMPOFLUX 3 direct flush WC valve

Ref. 763BOX-763000

Recessed in a waterproof box. Satin st. steel



DESCRIPTION

TEMPOFLUX 3 direct flush WC valve - Ref.763BOX-763000

TEMPOFLUX 3 recessed time flow direct flush valve: Satin finish stainless steel wall plate 210 x 162mm.

Waterproof recessing housing:

- Collar with waterproof seal.
- Hydraulic connection to the outside and maintenance from the front.
- Adjusts to all types of installation (rails, solid walls, panels).
- Compatible with wall finishes from 10 - 120mm (while maintaining the minimum recessing depth of 93mm).
- Suitable for standard or "pipe-in-pipe" supply.
- Stopcock and flow rate adjustment, activation unit and cartridge are all integrated and accessible from the front.
- TEMPOFLUX 3 F3/4" flush valve is compatible with sea water and grey water.
- Back flow prevention device inside the housing.
- Supplied in 2 kits: secure system flush without sensitive elements.

Soft-touch operation.

AB Anti-blocking system: flush only takes place once the push-button is released.

Dual flush 3L/6L can be adjusted to 2L/4L.

Outlet connection for PVC tube Ø 26/32mm.

Acoustic level complies with European standard EN 12541 (class II acoustic level).

Base flow rate: 1 l/sec.

Suitable for rimless WC pans without flow rate regulation and suitable for people with reduced mobility.

10-year warranty.

Kit contents: (763BOX): recessed housing with cover, valve configured for system flush, vacuum breaker, stopcock, connection accessories. (763000): control plate, collar for waterproofing, time flow cartridge.

ADVANTAGES



Soft-touch operation



Direct flush: no standing water



Dual flush 3L/6L



Waterproof housing, adjustable and modular

TECHNICAL CHARACTERISTICS

TEMPOFLUX 3 direct flush WC valve - [Ref.763BOX-763000](#)

| | |
|------------|------------------------------|
| Technology | Time flow |
| Inaltime | 210 mm |
| Conector | F3/4" |
| Finisaj | Stainless steel satin finish |
| Width | 162 mm |
| Depth | 93 - 190 mm |