DELABIE

TEMPOFLUX 3 direct flush WC valve



Ref. 763BOX-763000

Recessed in a waterproof box. Satin st. steel

DESCRIPTION

TEMPOFLUX 3 direct flush WC valve - Ref.763BOX-763000

TEMPOFLUX 3 recessed time flow direct flush valve: Satin finish stainless steel wall plate 210 x 162mm.
Waterproof recessing housing:
- Collar with waterproof seal.
- Hydraulic connection to the outside and maintenance from the front.
- Adjusts to all types of installation (rails, solid walls, panels).
- Compatible with wall finishes from 10 - 120mm (while maintaining the minimum recessing depth of 93mm).
- Suitable for standard or "pipe-in-pipe" supply.
- Stopcock and flow rate adjustment, activation unit and cartridge are all integrated and accessible from the front.
- TEMPOFLUX 3 F3/4" flush valve is compatible with sea water and grey water.
- Back flow prevention device inside the housing.
- Supplied in 2 kits: secure system flush without sensitive elements.

Soft-touch operation.
AB Anti-blocking system:flush only takes place once the push-button is released.
Dual flush 3L/6L can be adjusted to 2L/4L.
Outlet connection for PVC tube Ø 26/32mm.
Acoustic level complies with European standard EN 12541 (class II acoustic level).
Base flow rate: 1 l/sec.
Suitable for rimless WC pans without flow rate regulation and suitable for people with reduced mobility.
10-year warranty.
Kit contents: (763BOX): recessed housing with cover, valve configured for system flush, vacuum breaker, stopcock, connection accessories. (763000): control plate, collar for waterproofing, time flow cartridge.

ADVANTAGES

- Soft-touch operation
- Direct flush: no standing water
- Dual flush 3L/6L
- Waterproof housing, adjustable and modular

© Delabie

TECHNICAL CHARACTERISTICS

TEMPOFLUX 3 direct flush WC valve - Ref.763BOX-763000

Technology	Time flow
Inaltime	210 mm
Conector	F3/4"
Finisaj	Stainless steel satin finish
Width	162 mm
Depth	93 - 190 mm

© Delabie