

TEMPOMATIC 4 electronic tap

Ref. 443400

Recessed mains supply



DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref.443400

Wall-mounted electronic basin tap:
230/6V recessed mains supply.
Reduced-stagnation solenoid valve and electronic unit integrated into the body of the tap.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Duty flush (~60 seconds every 24 hours after last use).
Active, infrared presence detection, sensor at the end of the spout optimises detection.
Chrome-plated metal body L. 130mm.
Cap fixed in place by 2 concealed screws.
Stopcock.
Wall-mounted fixings.
Recessed inlet.
Anti-blocking security.
Suitable for people with reduced mobility.
10-year warranty.

ADVANTAGES



Total hygiene: no manual contact



90% water savings



Recessed mains supply



Anti-bacterial duty flush

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref.443400

Technology	Electronic
Debit	3 lpm
Conector	M1/2"
Supply	230/6V mains supply (recessed)
Spout Length	130 mm
Installation:	Wall-mounted

