DELABIE

BINOPTIC MIX electronic mixer

Ref. 378MCH15

Mains supply, Ø 15mm conical inlets



DESCRIPTION

BINOPTIC MIX electronic mixer - Ref.378MCH15

Deck-mounted electronic basin mixer:
Independent IP65 electronic control unit.
230/12V mains supply with transformer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
Active, infrared movement detection, sensor at the end of the spout optimises detection.
Chrome-plated solid brass body.
PEX flexibles with filters, solenoid valves and Ø 15mm conical inlets.
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Spout with a smooth interior and low volume of water (limits bacterial niches).
Side temperature control with adjustable maximum temperature limiter.
10-year warranty.


ADVANTAGES

- 90% water savings
- Hygiene lever: no manual contact
- Independent IP65 electronic control unit
- Anti-bacterial proliferation duty flush

TECHNICAL CHARACTERISTICS

BINOPTIC MIX electronic mixer - Ref.378MCH15

Technology	Electronic
Debit	3 lpm
Supply	230/12V mains supply
Drop Height	110 mm
Spout Length	135 mm
Installation:	Deck-mounted



© Delabie