

SECURITHERM BIOCLIP thermostatic basin mixer

Ref. H9605610L

Single hole, sequential thermostatic mixer H. 85mm L. 120mm



DESCRIPTION

SECURITHERM BIOCLIP thermostatic basin mixer - [Ref.H9605610L](#)

Deck-mounted SECURITHERM thermostatic basin mixer.
BIOCLIP: can be easily removed for cleaning and disinfection.
Sequential thermostatic mixer: opens and closes with cold water.
Single hole mixer with straight spout, H. 85mm L. 120mm, fitted with a hygienic flow straightener, with no build-up of impurities and withstands thermal shocks.
Anti-scalding failsafe: shuts off automatically if cold or hot water supply fails.
Securitouch thermal insulation prevents burns.
No risk of cross flow between the hot and cold water.
No non-return valves on the inlets.
Scale-resistant sequential thermostatic cartridge for single control adjustment of flow rate and temperature.
Adjustable temperature from cold water up to 40°C with maximum temperature limiter set at 40°C.
Thermal and chemical shocks are possible.
Spout and body with smooth interiors and low water volume.
Flow rate regulated at 7 lpm.
No manual contact thanks to Hygiene control lever L. 100mm.
Without pop-up waste.
Supplied with copper tails and chrome-plated brass stopcocks.
Reinforced fixing via 2 stainless steel rods.
Ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Mixer suitable for people with reduced mobility.
10-year warranty.
Also available with PEX flexibles.

ADVANTAGES

TECHNICAL CHARACTERISTICS

SECURITHERM BIOCLIP thermostatic basin mixer - Ref.H9605610L

Technology	SECURITHERM BIOCLIP sequential Securitouch
Inaltime	178 mm
Debit	7 lpm
Conector	M1/2" Ø 15mm
Finisaj	Chrome-plated brass
Drop Height	85 mm
Spout Length	120 mm
Temperature limiter	40 °C

