

BINOPTIC electronic tap

Ref. 370SBOX-370100

Mains supply



DESCRIPTION

BINOPTIC electronic tap - Ref.370SBOX-370100

Recessed electronic basin tap:

Mains supply with 230/6V (cable and transformer supplied).

Satin stainless steel plate 145 x 145mm with integrated electronics.

Recessed waterproof housing:

- Collar with waterproof seal.
 - Hydraulic connection from the exterior and maintenance from the front.
 - Modular installation (rails, solid walls, panels).
 - Compatible with walls from 10 to 120mm (whilst maintaining the minimum recessing depth of 83mm).
 - Adaptable standard pipework or "pipe in pipe".
 - Integrated stopcock and flow rate adjuster, filter and solenoid valve are accessible from the front.
 - BINOPTIC tap F½".
 - Supplied in 2 kits: secured system purge without sensitive elements.
- Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm.
- Scale-resistant flow straightener.
- Duty flush every 24 hours (can be adjusted to 12 hours or OFF) after the last use.
- Active, infrared presence detection, sensor at the end of the spout optimises detection.
- Anti-blocking security.
- Smooth interior spout with low volume of water (limits bacterial niches).
- Suitable for people with reduced mobility.
- 10-year warranty.

Kit composition:

(370SBOX): protected recessed housing, control is configured for system flush, connection accessories.

(370100): spout and plate, transformer, waterproof collar, control, solenoid valve, filter and stopcock.

ADVANTAGES



Total hygiene: no manual contact



90% water savings



Adjustable and modular waterproof housing



Concealed fixings

TECHNICAL CHARACTERISTICS

BINOPTIC electronic tap - [Ref.370SBOX-370100](#)

Technology	Electronic
Lungime	190 mm
Conector	F1/2"
Finisaj	Satin stainless steel
Installation:	Reccesed

