DELABIE

TEMPOMIX 3 time flow mixer

Ref. 79400015

Soft-touch operation, Ø 15mm stopcocks



DESCRIPTION

TEMPOMIX 3 time flow mixer - Ref.79400015

Deck-mounted single control time flow basin mixer:
Soft-touch operation.
Temperature control and operation on the push-button.
Time flow pre-set at ~7 seconds.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm.
Tamperproof scale-resistant flow straightener.
Chrome-plated solid brass body.
PEX flexibles with stopcocks, filters, non-return valves and Ø 15mm conical inlets.
Fixing reinforced by 2 stainless steel rods.
Adjustable maximum temperature limiter.
Suitable for people with reduced mobility.
10-year warranty.

*Add CR to the end of the reference (79400015CR) to order with copper tails.


ADVANTAGES

- Soft-touch operation
- 85% water savings
- Chrome-plated solid brass, reinforced fixings
- Sleek design

TECHNICAL CHARACTERISTICS

TEMPOMIX 3 time flow mixer - Ref.79400015

Technology	Time flow
Debit	3 lpm
Drop Height	70 mm
Spout Length	105 mm
Installation:	Deck-mounted



© Delabie