

OUTDOOR column

Ref. 717511

Time flow, 1 shower and 1 foot-rinse



DESCRIPTION

OUTDOOR column - Ref.717511

Time flow shower column:
 Anodised aluminium shower column ready to fit.
 Fitted with one shower and one foot-rinse.
 Bottom inlet via stopcock F $\frac{3}{4}$ ".
 TEMPOSOF 2 time flow valves for mixed water supply.
 Soft-touch operation.
 Time flow ~15 seconds.
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.
 Stainless steel foot-rinse with flow rate 3 lpm at 3 bar.
 Time flow ~7 seconds.
 Filters.
 Access panel with isolation valve and purge.
 Can easily be protected or taken apart in winter.
 Suitable for people with reduced mobility.
 10-year warranty.

ADVANTAGES

-  80% water savings
-  Soft-touch operation
-  Anti-corrosion anodised aluminium
-  Supplied ready to fit

TECHNICAL CHARACTERISTICS

OUTDOOR column - Ref.717511

Technology	Time flow
Inaltime	2245 mm
Debit	6 lpm
Conector	F3/4"
Finisaj	Aluminium

