

TEMPOMIX 3 shower mixer

Ref. 794BOX1-794218

Time flow single control, top inlet



DESCRIPTION

TEMPOMIX 3 shower mixer - Ref.794BOX1-794218

Recessed time flow shower mixer with soft-touch operation:
Tamperproof chrome-plated metal wall plate 160 x 160mm.

Waterproof recessing housing:

- Collar with waterproof seal.
- Hydraulic connection from the exterior and maintenance from the front.
- Top inlet.
- Adjusts to all types of installation (rails, solid walls, panels).
- Compatible with wall finishes 10 - 120mm (while maintaining the minimum recessing depth of 93mm).
- Suitable for standard pipe supply or "pipe in pipe".
- Stopcocks and flow rate adjustment, filters, non-return valves and cartridge are integrated and can be accessed from the front.
- TEMPOMIX 3 single control mixer F½".
- Supplied in 2 kits: secure system flush without sensitive elements.
- Temperature control and operation via the push-button.
- Maximum temperature limiter (can be adjusted by installer).
- Time flow ~30 seconds, can be adjusted.
- Soft-touch operation.
- Flow rate 9 lpm at 3 bar.
- Suitable for people with reduced mobility.
- 10-year warranty.

Kit contents:

(794BOX1): recessed housing with cover, valve with temporary caps configured for system flush and connection accessories.

(794218): control plate, valve, collar for waterproofing.

ADVANTAGES



Soft-touch operation



Recessed installation,
concealed fixings



Adjustable, modular
waterproof housing



Time flow system tested to
over 500,000 operations

TECHNICAL CHARACTERISTICS

TEMPOMIX 3 shower mixer - Ref.794BOX1-794218

Technology	Time flow
Inaltime	160 mm
Debit	9 lpm
Conector	1/2"
Width	160 mm
Depth	93 - 190 mm

