DELABIE

TEMPOMIX

Ref. 790BOX-790218

Time flow single control



DESCRIPTION

TEMPOMIX - Ref.790BOX-790218

Recessed time flow shower mixer:
Tamperproof bright polished stainless steel wall plate 160 x 220mm.
Waterproof recessing housing.
10 - 30mm allowance for different wall finishes.
TEMPOMIX ¾" single control mixer.
Ligature-resistant collar.
Temperature control and operation via the control.
Maximum temperature limiter (can be adjusted by the installer).
Time flow ~30 seconds, soft-touch operation.
Flow rate 6 lpm at 3 bar, can be adjusted.
Concealed fixings, stopcocks M½".
Chrome-plated metal control.
Integrated non-return valves and filters.
10-year warranty.

Kit contents:
(790BOX): recessed housing with cover, valve configured for system flush, stopcocks and connection accessories.
(790218): control plate, valve, time flow cartridge, collar for waterproofing.


ADVANTAGES


- Wall recessed installation
- System tested to over 500,000 operations
- 80% water savings
- Soft-touch operation

TECHNICAL CHARACTERISTICS

TEMPOMIX - Ref.790BOX-790218

Technology	Time flow
Inaltime	160 mm
Debit	6 lpm
Conector	1/2"
Width	220 mm
Water supply	Concealed





© Delabie