

TEMPOMIX shower kit



Ref. 790709

Single control time flow







DESCRIPTION

TEMPOMIX shower kit - Ref.790709

Recessed time flow shower kit:
 Stainless steel wall plate 160 x 160mm.
 Standard recessing housing.
 Recessing depth can be adjusted from 28 to 48mm.
 TEMPOMIX 3/4" single control mixer.
 Ligature-resistant collar.
 Temperature control and operation via the push-button.
 Maximum temperature limiter (can be adjusted by the installer).
 Time flow ~30 seconds, soft-touch operation.
 Flow rate 6 lpm at 3 bar.
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
 M1/2" connections for copper tubes Ø 14mm.
 Integrated non-return valves and filters.
 Chrome-plated metal control.
 10-year warranty. This model does not have a waterproof recessing box.
 The installer must ensure that the recessing area is waterproof and any leaks or condensates can drain away (see installation guide).

ADVANTAGES

-  80% water savings
-  Time flow system tested to over 500000 operations
-  Wall recessed installation
-  Soft-touch operation

TECHNICAL CHARACTERISTICS

TEMPOMIX shower kit - Ref.790709

Technology	Time flow
Inaltime	160 mm
Lungime	160 mm
Debit	6 lpm
Conector	1/2"
Width	160 mm
Heith	160 mm

