

## SECURITHERM shower panel

Ref. 79230015

Thermostatic time flow

### DESCRIPTION

#### SECURITHERM shower panel - Ref.79230015

Time flow thermostatic shower panel:  
 Anodised aluminium shower panel for wall-mounted, exposed installation.  
 Top inlet via in-line stopcocks and conical Ø 15mm inlets.  
 SECURITHERM thermostatic mixer.  
 Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C  
 Anti-scalding safety: automatic shut-off if cold or hot water supply fails.  
 Anti-cold showers function: automatic shut-off if hot water fails.  
 Thermal shocks are possible.  
 Soft-touch operation.  
 Time flow ~30 seconds.  
 Flow rate 6 lpm at 3 bar.  
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.  
 Concealed fixings.  
 Filters and non-return valves.  
 Suitable for people with reduced mobility.  
 10-year warranty.





### TECHNICAL CHARACTERISTICS

#### SECURITHERM shower panel - Ref.79230015

Technology	Time flow
Inaltime	1050 mm
Debit	6 lpm
Conector	M1/2" Ø 15mm
Finisaj	Aluminium
Temperature limiter	Thermostatic
Width	210 mm
Depth	65 mm
Water supply	In-line



### ADVANTAGES

-  Thermostatic control
-  Instant shut-off if cold water supply fails
-  80% water savings
-  Aluminium panel, brass controls

