DELABIE

SECURITHERM shower panel

Ref. 792313CF

Time flow thermostatic, comfort 10 lpm



DESCRIPTION

SECURITHERM shower panel - Ref.792313CF

Thermostatic time flow shower panel:
Large model stainless steel shower panel for wall mounted, exposed installation.
Concealed inlet via flexibles M1/2".
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
Anti-scalding safety: automatic shut-off if cold or hot water supply fails.
Thermal shocks are possible.
Soft-touch operation.
Time flow ~30 seconds.
Flow rate 10 lpm at 3 bar.
Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
M1/2" stopcocks.
Concealed fixings.
Filters and non-return valves.
10-year warranty.


ADVANTAGES

- Thermostatic temperature regulation
- Immediate shut-off if cold water fails
- Stainless steel sheath, brass controls
- 80% water savings

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref.792313CF

Technology	Time flow
Inaltime	1220 mm
Debit	10 lpm
Conector	M1/2"
Finisaj	Stainless steel
Temperature limiter	Thermostatic
Width	250 mm
Depth	100 mm
Water supply	Concealed



© Delabie