

## TEMPOFIX 3 frame system for urinals

Ref. 543006D-430016

Battery-operated electronic valve - For urinals with flexible ½"



### DESCRIPTION

#### TEMPOFIX 3 frame system for urinals - Ref.543006D-430016

Frame system with electronic urinal valve:  
Black powder-coated steel frame for wall-mounted installation.  
Fixes to floor and load-bearing walls, anchoring bolts supplied.  
Adjustable bracket from 95 - 280mm.  
Frame height can be adjusted from 0 - 200mm.  
Ø 50mm soil pipe with waterproof seal.  
Delivered pre-mounted.  
Compatible with solid wall finishes 10 - 120mm.  
10-year warranty.

Fitted with TEMPOMATIC 4 F½" electronic valve:  
Battery-operated with 123 6V Lithium battery.  
Stainless steel wall plate 145 x 145mm with integrated electronics.  
Shock-resistant infrared presence detection sensor.  
Waterproof recessing housing.  
Detection delay is 10 seconds.  
3 programmes (rinsing volume can be set according to urinal type).  
High frequency mode (exclusive to DELABIE).  
Hygienic duty flush every 24 hours (can be adjusted to 12 hours or Off) after last use: prevents vacuums.  
Flow rate pre-set at 0.15 L/sec at 3 bar, can be adjusted.  
Connection with ½" brass connection (for urinals supplied by flexibles).

Technical features: see TEMPOMATIC 4 urinal ref. 430PBOX-430016.

#### Kit contents:

(543006D): frame system, tube with brass union ½" for flexible supply, 1 sleeve for soil pipe Ø 50mm, recessed housing with cover, valve configured for system flush, connection accessories.

(430016): control plate, 6V lithium batteries, collar for waterproofing, valve, solenoid valve, filter and stopcock.

### ADVANTAGES



Total hygiene: no manual contact



3 rinsing programmes and high frequency mode



Easy and quick to install: supplied pre-mounted



Hygienic duty flush

## TECHNICAL CHARACTERISTICS

### TEMPOFIX 3 frame system for urinals - [Ref.543006D-430016](#)

Technology	Electronic
Inaltime	985 - 1385 mm
Conector	1/2"
Finisaj	Bright stainless steel
Supply	6V batteries
Width	430 mm
Depth	160 - 220 mm

