DELABIE

TEMPOFIX 3 frame system for urinals



Ref. 543006D-430006

Battery-operated electronic valve - For urinals with flexible ½"

DESCRIPTION

TEMPOFIX 3 frame system for urinals - Ref.543006D-430006

Frame system with electronic urinal valve:
Black powder-coated steel frame for wall-mounted installation.
Fixes to floor and load-bearing walls with anchoring bolts supplied.
Adjustable bracket 95 - 280mm.
Frame height can be adjusted from 0 - 200mm.
Ø 50mm soil pipe with waterproof seal.
Delivered pre-mounted.
Compatible with wall finishes 13 - 120mm.
10-year warranty.

Fitted with TEMPOMATIC 4 F½" direct flush electronic valve:
Operated by 123 6V Lithium batteries.
Satin stainless steel plate 145 x 145mm with integrated electronics.
Shock-resistant infrared presence detection sensor.
Waterproof recessing housing.
Detection delay is 10 seconds.
3 programmes (rinsing volume can be adjusted according to urinal type).
High frequency mode (exclusive to DELABIE).
Hygienic duty flush every 24 hours (can be adjusted to 12 hours or OFF) after last use: prevents vacuums.
Flow rate pre-set at 0.15 L/sec at 3 bar, can be adjusted.
Connection with ½" brass connection (for urinal valves with flexible supply).

Technical features: see TEMPOMATIC urinal ref. 430PBOX-430006.

Kit contents:
(543006D): frame system, tube with brass union ½" for flexible supply, sleeve for soil pipe Ø 50mm, recessed housing with cover, valve configured for system flush, connection accessories.
(430006): control plate, 6V lithium battery, collar for waterproofing, valve, solenoid valve, filter and stopcock.

ADVANTAGES


- Total hygiene: no manual contact
- 3 rinsing programmes and high frequency mode
- Easy and quick to install: supplied pre-mounted
- Hygienic duty flush

© Delabie

TECHNICAL CHARACTERISTICS

TEMPOFIX 3 frame system for urinals - Ref.543006D-430006

Technology	Electronic
Inaltime	985 - 1385 mm
Conector	1/2"
Finisaj	Satin stainless steel
Supply	6V batteries
Width	430 mm
Depth	160 - 220 mm



© Delabie