

## TEMPOMATIC 4 urinal valve

Ref. 479411

Electronic with integrated battery



### DESCRIPTION

#### TEMPOMATIC 4 urinal valve - Ref.479411

Exposed electronic urinal valve with integrated battery:  
 Battery-operated with integrated 223 6V Lithium battery.  
 For wall-mounted, exposed installation.  
 Reduced-stagnation solenoid valve and electronic unit integrated into the valve body.  
 Shockproof infrared presence detection sensor.  
 Detection delay is 10 sec.  
 3 programmes (rinsing volume adjustable in accordance to the type of urinal).  
 High-frequency mode (exclusive to DELABIE):  
 - short rinse after each user  
 - complementary rinse after busy period.  
 Hygienic duty flush, every 24hr after last use, prevents vacuums in the siphon.  
 Flow rate 0.15 L/sec. at 3 bar, can be adjusted.  
 Integrated stopcock and flow rate adjuster.  
 One-piece chrome-plated metal body.  
 M $\frac{1}{2}$ " connection.  
 Angled for recessed supply, outlet M $\frac{1}{2}$ ".  
 Suitable for people with reduced mobility.  
 10-year warranty.





Ideal for replacing old installations:  
 Can easily be installed where there was previously a time flow urinal.

### TECHNICAL CHARACTERISTICS

#### TEMPOMATIC 4 urinal valve - Ref.479411

|            |             |
|------------|-------------|
| Technology | Electronic  |
| Inaltime   | 150 mm      |
| Debit      | 0.15 l/sec. |
| Conector   | M1/2"       |
| Supply     | 6V battery  |
| Depth      | 70 mm       |

### ADVANTAGES

-  Total hygiene: no manual contact
-  High-frequency mode
-  Battery integrated into the valve body
-  Hygienic duty flush

