

## TEMPOMATIC 4 urinal valve

Ref. 479412

Electronic with integrated battery



### DESCRIPTION

#### TEMPOMATIC 4 urinal valve - Ref.479412

Exposed electronic urinal valve with integrated battery:  
Battery-operated with integrated 223 6V Lithium battery.  
For wall-mounted, exposed installation.  
Reduced-stagnation solenoid valve and electronic unit integrated into the valve body.  
Shockproof infrared presence detection sensor.  
Detection delay is 10 sec.  
3 programmes (rinsing volume adjustable in accordance to the type of urinal).  
High-frequency mode (exclusive to DELABIE):  
- short rinse after each user  
- complementary rinse after busy period.  
Hygienic duty flush, every 24hr after last use, prevents vacuums in the siphon.  
Flow rate 0.15 L/sec. at 3 bar, can be adjusted.  
Integrated stopcock and flow rate adjuster.  
One-piece chrome-plated metal body.  
M1/2" connection.  
Angled for recessed supply with Ø 35mm neck tube.  
For standard urinals: 50mm gap from wall.  
Suitable for people with reduced mobility.  
10-year warranty.

Ideal for replacing old installations:  
Can easily be installed where there was previously a time flow urinal.

### ADVANTAGES



Total hygiene: no manual contact



High-frequency mode



Battery integrated into the valve body



Hygienic duty flush

## TECHNICAL CHARACTERISTICS

### TEMPOMATIC 4 urinal valve - Ref.479412

Technology	Electronic
Inaltime	450 mm
Debit	0.15 l/sec.
Conector	M1/2"
Supply	6V battery
Depth	85 mm
Width to the wall	50 mm

