

TEMPOMATIC urinal valve

Ref. 477000

Electronic valve with mains supply



DESCRIPTION

TEMPOMATIC urinal valve - Ref.477000

Exposed electronic urinal valve:

Mains supply, electronic unit 12V, solenoid valve, stopcock and flow rate adjuster M $\frac{1}{2}$ ".

White powder-coated stainless steel wall box.

Shockproof infrared presence detection.

Detection delay is 3 sec.

Automatic pre-rinse is possible.

Time flow 3 sec., can be adjusted from 3 to 12 sec.

Hygienic duty flush, every 24hr after last use, prevents vacuums in the siphon.

Flow rate 0.3 l/sec. at 3 bar pressure, can be adjusted.

Order transformer separately 230/12V.

Straight for in-line supply, outlet M $\frac{1}{2}$ ".

Suitable for people with reduced mobility.

10-year warranty.

ADVANTAGES



Total hygiene: no manual contact



ECO time flow set at 3 seconds



Electronic unit



Automatic anti-bacterial proliferation duty flush

TECHNICAL CHARACTERISTICS

TEMPOMATIC urinal valve - Ref.477000

Technology	Electronic
Inaltime	205 mm
Debit	0.3 l/sec
Conector	M1/2"
Supply	230/12V mains supply
Width	250 mm
Depth	65 mm

