

## TEMPOMATIC urinal valve

Ref. 428150

Electronic mains supply



### DESCRIPTION

#### TEMPOMATIC urinal valve - Ref.428150

Cross wall electronic urinal valve:

Mains supply, electronic control unit 12V with solenoid valve, filter and stopcock M $\frac{1}{2}$ ".

Cross wall installation for walls ? 155mm.

Shock-resistant infrared presence detector.

Detection distance, time flow and flow rate can be adjusted during installation.

Order the 230/12V transformer separately.

Presence detection delay is 3 sec.

Automatic pre-rinse possible.

Time flow 3 seconds, can be adjusted from 3 - 12 sec.

Hygienic duty flush every 24 hours after last use, prevents vacuums.

Flow rate 0.3 L/sec. at 3 bar pressure, can be adjusted.

Wall plate flush to the wall.

Threaded rods can be cut-to-size.

Suitable for people with reduced mobility.

10-year warranty.

### ADVANTAGES



Total hygiene: no manual contact



ECO time flow set at 3 seconds



Cross wall installation



Hygienic duty flush

### TECHNICAL CHARACTERISTICS

#### TEMPOMATIC urinal valve - Ref.428150

Technology	Electronic
Lungime	155 mm
Debit	0.3 l/sec
Conector	1/2"
Supply	12V mains supply

