

TEMPOMATIC urinal valve

Ref. 428200

Electronic mains supply







DESCRIPTION

TEMPOMATIC urinal valve - Ref.428200

Recessed electronic urinal valve:
 Mains supply, electronic control unit 12V with solenoid valve, filter and stopcock M $\frac{1}{2}$ ".
 Cross wall installation for walls ? 225mm.
 Shock-resistant infrared presence detector.
 Detection distance, time flow and flow rate can be adjusted at installation.
 Order the 230/12V transformer separately.
 Presence detection delay is 3 seconds.
 Automatic pre-rinse possible.
 Time flow 3 sec. can be adjusted from 3 - 12 seconds.
 Hygienic duty flush is possible every 24 hours after last use, prevents vacuums.
 Flow rate 0.3 L/sec. at 3 bar pressure, can be adjusted.
 Wall plate flush to the wall.
 Threaded rods can be cut-to-size.
 Suitable for people with reduced mobility.
 10-year warranty.

ADVANTAGES

-  Total hygiene: no manual contact
-  ECO time flow set at 3 seconds
-  Cross wall installation
-  Hygienic duty flush

TECHNICAL CHARACTERISTICS

TEMPOMATIC urinal valve - Ref.428200

Technology	Electronic
Lungime	225 mm
Debit	0.3 l/sec
Conector	1/2"
Supply	Secteur 12V

