

TEMPOMATIC urinal valve

Ref. 428156

Electronic, battery-operated



DESCRIPTION

TEMPOMATIC urinal valve - Ref.428156

Cross wall electronic urinal valve:
6V lithium battery-operated, electronic control unit with solenoid valve, filter and stopcock M $\frac{1}{2}$ ".

Cross wall installation ? 155 mm.

Shock-resistant infrared presence detection sensor.

Detection distance, time flow and flow rate can be adjusted during installation.

Detection delay is 3 seconds.

Automatic pre-rinse is possible.

Time flow ~3 seconds, can be adjusted from 3 - 12 seconds.

Hygienic duty flush every 24 hours after last use: prevents vacuums.

Flow rate 0.3 L/sec. at 3 bar, can be adjusted.

Wall plate flush to the wall.

Threaded rod can be cut to size.

Suitable for people with reduced mobility.

10-year warranty.

ADVANTAGES



Total hygiene: no manual contact



ECO time flow set at 3 seconds



Cross wall installation



Hygienic duty flush

TECHNICAL CHARACTERISTICS

TEMPOMATIC urinal valve - Ref.428156

Technology	Electronic
Lungime	155 mm
Debit	0.3 l/sec
Conector	1/2"
Supply	6V battery
Supply	6V batteries

